


NEVADA



PRIMJENA usis i tlak vina i svih drugih prehrambenih tekućina
MATERIJAL CIJEVI: prozirni atoksični plastificirani PVC
OJAČANJE: tvrdi PVC crvene boje otporan na gaženje
TEMPERATURA: -10 +60 °C

Promjer (mm)	Radni tlak (bar)	Rasprs. tlak (bar)	Težina (kg/m)	Pol. sav. (mm)	Kolut (m)	Montaža	
						Obujmice	
20	9.0	27.0	0.300	100	50	18 23 - 25	Inox
25	9.0	27.0	0.410	120	50	20 29 - 31	Inox
30	9.0	27.0	0.550	160	50	20 32 - 35	Inox
32	9.0	27.0	0.520	230	50	20 36 - 39	Inox
35	9.0	27.0	0.630	180	50	20 40 - 43	Inox
38	8.0	24.0	0.700	200	50	22 44 - 47	Inox
40	8.0	24.0	0.730	200	50	22 48 - 51	Inox
45	7.0	21.0	0.840	230	50	22 52 - 55	Inox
50	6.0	18.0	1.000	250	50	22 56 - 59	Inox
55	8.0	24.0	1.270	370	50	22 64 - 67	Inox
60	6.0	18.0	1.280	320	50	23 68 - 73	Inox
63	5.5	15.5	1.460	350	50	23 68 - 73	Inox
70	4.5	13.5	1.600	400	50	23 74 - 79	Inox
76	4.5	13.5	1.730	440	50	23 80 - 85	Inox
80	4.0	12.0	1.850	480	50	23 86 - 91	Inox
90	4.0	12.0	2.100	550	30	23 98 - 103	Inox
102	3.5	10.5	2.660	620	30	23 113 - 121	Inox
110	3.5	10.5	3.000	650	30	23 122 - 130	Inox
120	3.0	9.0	3.300	700	30	23 131 - 139	Inox
127	3.0	9.0	3.500	720	30	23 140 - 148	Inox
152	3.0	9.0	4.650	820	30	23 149 - 161	Inox
200	4.0	12.0	10.300	2100	30	23 201 - 213	Inox

BAND - IT